


# ProPatch®

## COLD MIX



ProPatch® Cold Mix is high performance patching material formulated using 1/4 chip aggregate and high quality modified cutback asphalt. Designed for potholes, street edges, utility cuts, and large cracks, ProPatch® Cold Mix is an easy to apply, year round, permanent asphalt repair solution.

## Features and Benefits:

ProPatch® Cold Mix works in all weather conditions and no special equipment is required. ProPatch® Cold Mix is designed to remain workable at sub-zero temperatures.

As a high performance cold mix, ProPatch® is designed to:

- Bond securely with road surfaces.
- Form a permanent surface that is instantly ready for traffic.
- Remain pliable, workable, and compactable at air temperatures as low as 14°F/-10°C.
- Remains in the pothole saving time and money compared to conventional cold mix.



### General Properties and Guidelines:

<b>Appearance</b>	Asphalt coated aggregate
<b>Relative Density</b>	2.5-2.75 g/mL
<b>Cohesion Index</b>	Min 60
<b>Workability</b>	Flexible and Cohesive to 14°F/-10°C

Based on the Ecotoxicity Hazard Classification Categories from the US Fish and Wildlife Services, ProPatch® Cold Mix has been tested and classified as relatively harmless to aquatic life, using the EPA 821-R-02-021 and WAF test methods (ASTM 2004, OECD, 2000) by “AquaTox Testing & Consulting Inc.”

### Easy Application:

ProPatch® Cold Mix is quick and easy to apply using our simple P.A.C. approach.



#### PREPARE

Sweep away any loose aggregate and debris from the area.



#### APPLY

Fill the affected area with ProPatch® Cold Mix.



#### COMPACT

Apply pressure using a hand tamp.

The repaired surface is open to traffic immediately and will remain flexible below the road surface to accommodate bridge deck or ground movement. Following the application, ProPatch® Cold Mix becomes a permanent part of the roadway.